

MCB Accessories SERIES

SGBA Series MCB Accessory

SGSO Series Door Bell

SGSL Series Indicating Light



SGSL - 1 Series

Indicating Light

Standard	EN/IEC60947-5-1
Rated current AC12(A)	20
Electric ratings	Up to AC 230 50/60Hz
Rated insulation Voltage Ui(V)	500
Illumination	LED, Incandescence, neon
Life	Incandescence lamp $\geq 1000\text{h}$ Neon lamp $\geq 2000\text{h}$ LED $\geq 30000\text{h}$
Ambient temperature($^{\circ}\text{C}$)	$-5\sim+40$, max. 95% humidity
Storage temperature($^{\circ}\text{C}$)	$-40\sim+75$
Connection capacity(mm^2)	1-16
Color	Green, red, yellow, blue, white
Type of terminal	Pin type and Lug type
Protection degree	IP20
Mounting	35mm DIN rail



SGSL-1 Red



SGSL-1 Yellow



SGSL-1 Green

SGSL - 1 Series

Indicating Light

	Rated voltage (V)	Code NO.	Illumination	color	Packing unit
 SGSL-1 Red	AC/DC 6.3V	SGSL-1-G-L6	Neon incandescence LED	Green 	12
	AC/DC 12V	SGSL-1-G-L12			
	AC/DC 24V	SGSL-1-G-L24			
	AC/DC 110V	SGSL-1-G-L110			
	AC/DC 230V	SGSL-1-G-L230			
 SGSL-1 Yellow	AC/DC 6.3V	SGSL-1-R-L6	Neon incandescence LED	Red 	12
	AC/DC 12V	SGSL-1-R-L12			
	AC/DC 24V	SGSL-1-R-L24			
	AC/DC 110V	SGSL-1-R-L110			
	AC/DC 230V	SGSL-1-R-L230			
 SGSL-1 Green	AC/DC 6.3V	SGSL-1-Y-L6	Neon incandescence LED	Yellow 	12
	AC/DC 12V	SGSL-1-Y-L12			
	AC/DC 24V	SGSL-1-Y-L24			
	AC/DC 110V	SGSL-1-Y-L110			
	AC/DC 230V	SGSL-1-Y-L230			
	AC/DC 6.3V	SGSL-1-B-L6	Neon incandescence LED	Blue 	12
	AC/DC 12V	SGSL-1-B-L12			
	AC/DC 24V	SGSL-1-B-L24			
	AC/DC 110V	SGSL-1-B-L110			
	AC/DC 230V	SGSL-1-B-L230			
	AC/DC 6.3V	SGSL-1-W-L6	Neon incandescence LED	White 	12
	AC/DC 12V	SGSL-1-W-L12			
	AC/DC 24V	SGSL-1-W-L24			
	AC/DC 110V	SGSL-1-W-L110			
	AC/DC 230V	SGSL-1-W-L230			