

 TÜVRheinland® DIN CERTCO		 TÜVRheinland® Precisely Right.	
Certificate No.	R50681401 0001	Our Reference	01-Qif- CN254TIC 001
		Appendix No.	1
Constructional Data Form (CDF) for DC Contactor		(EN 60947-4-1)	Page 1 of 4

License holder: MAXGE ELECTRIC TECHNOLOGY CO., LTD.
 Full address: NO. 299 EAST CHANGHONG ROAD, DEQING ECONOMIC ZONE, WUKANG, DEQING, 313200 Zhejiang, P.R. China


Factory1 : MAXGE ELECTRIC TECHNOLOGY CO., LTD.
 Full address: NO. 299 EAST CHANGHONG ROAD, DEQING ECONOMIC ZONE, WUKANG, DEQING, 313200 Zhejiang, P.R. China

Factory2 : MAXGE ELECTRIC(WUHU)CO.,LTD
 Full address: NO.13-2,JIUZI AVENUE,ANHUI XINHU, ECONOMIC DEVELOPMENT ZONE,WANZHI DISTRICT, WUHU CITY, 241100 Anhui, P.R. China

Type or Model Number : SGC1-F115, SGC1-F150, SGC1-F185, SGC1-F225, SGC1-F265, SGC1-F330, SGC1-F400, SGC1-F500, SGC1-F630, SGC1-F800

Kind of device: AC Contactor

Type designation	SGC1-F115, SGC1-F150, SGC1-F185, SGC1-F225, SGC1-F265, SGC1-F330, SGC1-F400, SGC1-F500, SGC1-F630, SGC1-F800
Ambient temperature	-5 °C ~ 40 °C
Contact material	Copper
Interrupting medium	Air
Number of poles	3P
Utilization category	AC-3
Rated operational voltage (Ue)	380/400/415V, 690V
Frequency	50/60Hz
Rated operational current (Ie)	115A(SGC1-F115), 150A(SGC1-F150) 185A(SGC1-F185), 225A(SGC1-F225) 265A(SGC1-F265), 330A(SGC1-F330) 400A(SGC1-F400), 500A(SGC1-F500) 630A(SGC1-F630), 800A(SGC1-F800)

TÜV Rheinland Group 2025.06.09 	
(Date)	(Signature)
(Stamp and Signature of Applicant)	

Certificate No. R50681401 0001

Our Reference 01-Qif- CN254TIC 001

Appendix No. 1

Constructional Data Form (CDF) for DC Contactor (EN 60947-4-1)

Page 2 of 4

Conventional free air thermal current (Ith)	200A(SGC1-F115, SGC1-F150) 280A(SGC1-F185, SGC1-F225) 360A(SGC1-F265, SGC1-F330) 580A(SGC1-F400, SGC1-F500) 850A(SGC1-F630, SGC1-F800)
Conventional enclosed thermal current (Ithe)	/
Rated insulation voltage (Ui)	690V
Impulse withstand voltage (Uimp)	8kV
Overvoltage category	III
Conditional short-circuit current	Iq=50kA/690V(SGC1-F115, SGC1-F150) Iq=50kA/690V(SGC1-F185, SGC1-F225) Iq=50kA/690V(SGC1-F265, SGC1-F330) Iq=50kA/690V(SGC1-F400, SGC1-F500) Iq=50kA/690V(SGC1-F630, SGC1-F800)
Co-ordination type	Type 2
Short circuit protective device	Fuse: RS714C
IP code	/
Pollution degree	3
Rated duties	Uninterrupted duty, interrupted duty
Intermittent duty class	SGC1-F115, SGC1-F150: 300ops/h, SGC1-F185, SGC1-F225, SGC1-F265, SGC1-F330, SGC1-F400, SGC1-F500, SGC1-F630, SGC1-F800: 120ops/h
On-load factor	40%
Suitability for isolation	/
Pole impedance of a contactor (Z)	50 mΩ
Electromagnetic compatibility (EMC)	/

TÜV Rheinland Group
 2025.06.09

Felix Qi

(Date)

(Signature)

(Stamp and Signature of Applicant)


			
Certificate No.	R50681401 0001	Our Reference	01-Qif- CN254TIC 001
		Appendix No.	1
Constructional Data Form (CDF) for DC Contactor		(EN 60947-4-1)	Page 3 of 4

Terminals /connection:

Type designation	
Terminal designation, main circuit	1L1, 3L2, 5L3, 2T1, 4T2, 6T3
Terminal designation, auxiliary circuit	1NO, 1NC
Terminal designation, control circuit	A1, A2
Type of terminal, main circuit	Rigid
Type of terminal, auxiliary circuit	Rigid
Type of terminal, control circuit	Rigid
Rated cross sectional area, main circuit	10 mm ²
Rated cross sectional area, auxiliary circuit	0.2 mm ²
Type of conductor	Copper
Number of conductors per terminal	1
Required preparation of the conductor	Required
Tightening torque, main circuit (N•m)	1,2
Tightening torque, auxiliary circuit (N•m)	1,2
Tightening torque, control circuit (N•m)	1,2
Material/plating terminal, main circuit	Copper alloy
Material/plating terminal, auxiliary circuit	Copper alloy
Material/plating terminal, control circuit	Copper alloy

Control circuit (coil):

Type designation	
Insulation class	F
Kind of current/rated frequency	50/60Hz
Rated control circuit voltage	220/230/240V, 380/400/415V, 440V
Rated control supply voltage	220/230/240V, 380/400/415V, 440V
Coil power consumption(holding power Limit Value)	I

TÜV Rheinland Group 2025.06.09 	
(Date)	(Signature)
(Stamp and Signature of Applicant)	

Coil power consumption(pick-up power Limit Value)	/
---	---

Auxiliary circuit:

Type designation	/
Contact form	/
Utilization category	/
Operational voltage	/
Operational current	/
Insulation voltage	/
Conventional thermal current	/
Conditional short-circuit current	/
Short circuit protective device	/

Plastic insulating parts:

Component	Manufacturer	Material name	Flame class	PTI	Material Group
Cover	Jianyin Jihua New Material Co Ltd	PBT4308G29	Glow wire 850°C	175	III
Base	KINGFA SCI & TECH CO LTD	PBT-RG301	Glow wire 850°C	175	III